

SCHEDULE 1.

INSPECTION CRITERIA FOR TRUCKS, TRACTORS & BUSES

MINOR DEFECTS		MAJOR DEFECTS
AIR BRAKE ITEMS		
AIR PRESSURE BUILD UP TIME	1.2 - SLOW AIR PRESSURE BUILD UP TIME	
AUDIBLE LEAKS AIR LOSS RATE	1.1 - AUDIBLE AIR LEAKS	1.4M - AIR LOSS RATE EXCEEDS THE PERSCRIBED LIMIT
BRAKE ADJUSTMENT / PUSHROD STROKE		1.3M - PUSHROD STROKE OF ANY BRAKE EXCEEDS THE ADJUSTMENT LIMIT
TRACTOR PROTECTION VALVE		1.5M - INOPERATIVE TOWING VEHICLE TRACTOR PROTECTION SYSTEM
LOW AIR WARNING SYSTEM		1.6M - LOW AIR WARNING SYSTEM FAILS OR SYSTEM IS ACTIVATED
EXTERIOR ITEMS		
COUPLER FASTENERS	4.1 - COUPLER OR MOUNTING HAS LOOSE OR MISSING FASTENER	
COUPLER MOVEMENT		4.2M - COUPLER IS INSECURE OR MOVEMENT EXCEEDS THE PERSCRIBED LIMIT
COUPLER LOCK		4.3M - COUPLING OR LOCKING MECHANISM IS DAMAGED OR FAILS TO LOCK
CAB DOORS	2.1 - OCCUPANT COMPARTMENT DOOR FAILS TO OPEN	2.2M - OCCUPANT COMPARTMENT DOOR FAILS TO CLOSE SECURELY
EXHAUST LEAKS	10.1 - EXHAUST LEAK	10.2M - EXHAUST LEAK THAT CAUSES EXHAUST GAS TO ENTER THE OCCUPANT COMPARTMENT
FRAME & CARGO BODY	11.1 - DAMAGED FRAME OR CARGO BODY	11.2M - VISIBLY SHIFTED, CRACKED, COLLAPSING OR SAGGING FRAME MEMBER
FUEL SYSTEM	12.1 - MISSING FUEL TANK CAP	12.2M - INSECURE FUEL TANK 12.3M - DRIPPING FUEL LEAK
GLASS & MIRRORS	14.1 - REQUIRED MIRROR OR WINDOW GLASS FAILS TO PROVIDE THE REQUIRED VIEW TO THE DRIVER AS A RESULT OF BEING CRACKED, BROKEN, DAMAGED, MISSING OR MALADJUSTED 14.2 - REQUIRED MIRROR OR WINDOW GLASS HAS BROKEN OR DAMAGED ATTACHEMENTS ONTO VEHICLE BODY	
HYDRAULIC BRAKES (CLASS D)	17.1 - BRAKE FLUID IS BELOW MINIMUM INDICATED LEVEL	17.2M - PARKING BRAKE IS INOPERATIVE 17.3M - BRAKE BOOST OR POWER ASSIST IS NOT OPERATIVE 17.4M - BRAKE FLUID LEAK 17.5M - BRAKE PEDAL FADE / INSUFFICIENT PEDAL RESERVE 17.6M - ACTIVATED WARNING DEVICE OTHER THAN ABS 17.7M - BRAKE FLUID RESERVOIR LESS THAN ¼ FULL
AIR SUSPENSION	20.1 - AIR LEAK IN AIR SUSPENSION SYSTEM	20.4M - DAMAGED (PATCHED, CUT, BRUISED, CRACKED TO BRAID) INSECURELY MOUNTED OR DEFLATED AIR BAG
SPRING LEAF SUSPENSION	20.2 - A BROKEN SPRING LEAF	20.5M - CRACKED OR BROKEN MAIN SPRING LEAF OR MORE THAN ONE BROKEN SPRING LEAF IN ANY SPRING ASSEMBLY 20.6M - PART OF SPRING LEAF OR SUSPENSION IS MISSING, SHIFTED OUT OF PLACE OR IN CONTACT WITH ANOTHER VEHICLE COMPONENT
SUSPENSION FASTENERS	20.3 - SUSPENSION FASTENER IS LOOSE, MISSING OR BROKEN	20.7M - LOOSE U-BOLT

SCHEDULE 1.

INSPECTION CRITERIA FOR TRUCKS, TRACTORS & BUSES

	MINOR DEFECTS	MAJOR DEFECTS
TIRE LEAKS / INFLATION	21.2 - TIRE LEAKING, IF LEAK CANNOT BE HEARD. IF LEAK CAN BE FELT OR HEARD, TIRE IS TO BE TREATED AS A FLAT	21.3M - FLAT TIRE
TIRE TREAD / SIDEWALL CONDITION	21.1 - DAMAGED TREAD OR SIDEWALL OF TIRE	21.4M - TIRE TREAD DEPTH IS LESS THAN WEAR LIMIT 21.5M - TIRE IS IN CONTACT WITH ANOTHER TIRE OR ANY VEHICLE COMPONENT OTHER THAN A MUDFLAP 21.7M - TIRE HAS EXPOSED CORDS IN THE TREAD OR OUTER SIDEWALL AREA
WHEEL HUBS	22.1 - HUB OIL BELOW MINIMUM LEVEL WHEN FITTED WITH SIGHT GLASS 22.2 - LEAKING WHEEL SEAL	22.5M - EVIDENCE OF IMMEDIATE WHEEL HUB OR BEARING FAILURE
WHEEL FASTENERS		22.3M - WHEEL HAS LOOSE, MISSING OR INEFFECTIVE FASTENER 22.5M - EVIDENCE OF IMMEDIATE WHEEL HUB OR BEARING FAILURE
WHEEL RIM		22.4M - DAMAGED, CRACKED OR BROKEN WHEEL RIM OR ATTACHING PART 22.5M - EVIDENCE OF IMMEDIATE WHEEL HUB OR BEARING FAILURE
INTERIOR ITEMS		
DRIVER SEAT / BELT	7.1 - SEAT IS DAMAGED OR FAILS TO REMAIN IN SET POSITION	7.2M - SEAT BELT OR TETHER BELT IS INSECURE, MISSING OR MALFUNCTIONS
EMERGENCY EQUIPMENT	9.1 - EMERGENCY EQUIPMENT IS MISSING DAMAGED OR DEFECTIVE	
GLASS & MIRRORS	14.1 - REQUIRED MIRROR OR WINDOW GLASS FAILS TO PROVIDE THE REQUIRED VIEW TO THE DRIVER AS A RESULT OF BEING CRACKED, BROKEN, DAMAGED, MISSING OR MALADJUSTED 14.2 - REQUIRED MIRROR OR GLASS HAS BROKEN OR DAMAGED ATTACHEMENTS ONTO VEHICLE BODY	
HEATER / DEFROSTER	15.1 - CONTROL OR SYSTEM FAILURE	15.2M - DEFROSTER FAILS TO PROVIDE UNOBSTRUCTED VIEW THROUGH THE WINDSHIELD
WINDSHIELD WIPER WASHER SYSTEM	23.1 - CONTROL OR SYSTEM FAILURE 23.2 - WIPER BLADE IS DAMAGED, MISSING OR FAILS TO ADEQUATELY CLEAR DRIVERS FIELD OF VISION	23.3M - WHEN USE OF WIPER OR WASHER FLUID IS REQUIRED, WIPER OR WASHER FAILS TO ADEQUATELY CLEAR DRIVERS FIELD OF VISION IN AREA SWEEPED BY DRIVERS SIDE WIPER

PLEASE REFER TO THE COPY OF SCHEDULE 1 FOUND WITHIN YOUR DAILY VEHICLE INSPECTION REPORT FOR A COMPLETE LIST OF DEFECT CODES